

Electronic force sensing with sensor normalization

Patent Number: ☒ US5440237 ←
Publication date: 1995-08-08
Inventor(s): BROWN DANIEL R (US); BIEHL PHILIP D (US)
Applicant(s): INCONTROL SOLUTIONS INC (US)
Requested Patent: ☒ WO9428387 ← PCT PATENT FAMILY member
Application Number: US19930069717 19930601
Priority Number(s): US19930069717 19930601
IPC Classification: G04F10/00; G01L7/04
EC Classification: G01D18/00B2, G01L25/00
Equivalents:

Abstract

Methods and apparatus are disclosed for normalizing electronic sensor data to correct for variations in individual sensor transfer characteristics which are not known in advance. A general characteristic transfer function for a sensor type of interest is determined empirically. A baseline response reading is acquired from an individual sensor, and that baseline response applied to the general transfer function to determine a specific transfer function for the individual sensor. The specific transfer function is used to calculate normalized data. One application of the invention is in computer cursor control pointing devices such as a joystick. Because the invention compensates for wide variations in sensor characteristics, inexpensive sensors such as force-sensitive resistors may be used in a joystick without sacrificing pointing accuracy and ergonomic efficiency.

Data supplied from the esp@cenet database - I2

BEST AVAILABLE COPY



US005440237A

United States Patent [19][11] **Patent Number:** 5,440,237**Brown et al.**[45] **Date of Patent:** Aug. 8, 1995[54] **ELECTRONIC FORCE SENSING WITH
SENSOR NORMALIZATION**[75] **Inventors:** Daniel R. Brown, Beaver Creek;
Philip D. Biehl, Tigard, both of Oreg.[73] **Assignee:** InControl Solutions, Inc., Clackamas,
Oreg.[21] **Appl. No.:** 69,717[22] **Filed:** Jun. 1, 1993[51] **Int. Cl.⁶** G04F 10/00; G01L 7/04[52] **U.S. Cl.** 324/601; 324/130;
364/571.01[58] **Field of Search** 324/115, 73.1, 132,
324/74, 130, 601; 345/159, 161;
364/571.01-571.08[56] **References Cited****U.S. PATENT DOCUMENTS**

4,374,381	2/1983	Ng et al.	340/711
4,399,515	8/1983	Gross	364/571.04
4,446,715	8/1984	Bailey	364/571.02
4,716,536	12/1987	Blanchard	364/571.04
4,725,950	2/1988	Woods	364/571.06
5,012,231	4/1991	Felsenstein	340/709
5,095,453	3/1992	Pierson et al.	364/571.05
5,135,002	4/1992	Kirchner et al.	364/571.03
5,247,467	9/1993	Nguyen et al.	364/571.02
5,269,311	12/1993	Kirchner et al.	364/571.02
5,345,400	9/1994	Bissell et al.	364/571.01
5,347,476	9/1994	McBean, Sr.	364/571.04

FOREIGN PATENT DOCUMENTS

0302385A2 7/1988 European Pat. Off. .

0535907A2 4/1993 European Pat. Off. .

352370A1 6/1985 Germany .

3913648C1 4/1989 Germany .

PCT/US88/-

04545 12/1988 WIPO .

PCT/GB88/-

00822 4/1989 WIPO .

OTHER PUBLICATIONS

Lindahl, "A Digital compensation Technique for Pressure Transducers", 1982, pp. 343-344.

Primary Examiner—Ernest F. Karlson*Attorney, Agent, or Firm*—Marger, Johnson, McCollom
& Stelowitz[57] **ABSTRACT**

Methods and apparatus are disclosed for normalizing electronic sensor data to correct for variations in individual sensor transfer characteristics which are not known in advance. A general characteristic transfer function for a sensor type of interest is determined empirically. A baseline response reading is acquired from an individual sensor, and that baseline response applied to the general transfer function to determine a specific transfer function for the individual sensor. The specific transfer function is used to calculate normalized data. One application of the invention is in computer cursor control pointing devices such as a joystick. Because the invention compensates for wide variations in sensor characteristics, inexpensive sensors such as force-sensitive resistors may be used in a joystick without sacrificing pointing accuracy and ergonomic efficiency.

13 Claims, 8 Drawing Sheets